



## High-Accuracy GPS Receiver for Your Smartphone, Tablet, or Notebook Computer

*The Arrow Lite<sup>®</sup> is designed specifically to use with a variety of mobile devices, including your smartphone, tablet, or notebook computer. It incorporates rock-solid, wireless Bluetooth<sup>®</sup> technology that works with Android, iOS, and Windows<sup>®</sup> devices, making it obsolete-proof. Contemplating switching from an iPhone to an Android phone or vice-versa? No problem, the Arrow lite works smoothly with both.*

### Use the Mobile GIS Software of Your Choice

Seems like a new mobile GIS software is being offered each week? With the Arrow Lite you will not be tied to legacy GPS receiver hardware or GIS software, it will grow with you. The Arrow Lite feeds submeter accuracy to every app on your Android or iOS device, even Google or Apple maps! Esri Collector, AmigoCloud, Mapit, GeoJot, iCMTGIS, it works seamlessly with all of them and many more mapping apps.

### Real-time, Worldwide Accuracy

The Arrow Lite takes advantage of free GPS SBAS corrections in most regions of the world, North America is covered by WAAS, Europe and North Africa by EGNOS, India is covered by GAGAN, and Japan by MSAS. The above-mentioned free SBAS services provide 60 cm real-time accuracy.

# ARROW Lite<sup>®</sup>

ARROW Series<sup>®</sup>  
for Submeter GPS Positioning

### Key Features:

- Submeter GPS
- 100 % Android, iOS, Windows compatible
- 60 cm real-time accuracy using free SBAS
- Supports all mobile GIS softwares



### Works Where Other Receivers Can't

The Arrow Lite was designed specifically with GIS users in mind. It squeezes more accuracy from SBAS corrections than any other receiver in the world. With its patented technology, you can use it under trees, around buildings, and in rugged terrain where other receivers will fail to deliver. Your efficiency will be optimized because you will get real-time results in the field! No post-processing is required.



# Specifications

## GPS Sensor

|                              |   |
|------------------------------|---|
| Receiver Type:               | L1, C/A code, with carrier phase smoothing                                  |
| Channels:                    | 12-channel, parallel tracking   |
| SBAS Support:                | 2-channel, parallel tracking<br>WAAS, EGNOS, MSAS, GAGAN,<br>and compatible |
| Update Rate:                 | 1 Hz Default, optional 10 Hz, 20 Hz   |
| DGPS Horizontal Accuracy:    | < 60 cm 2dRMS, 95% confidence <sup>1</sup>                                  |
| Horizontal Accuracy:         | < 2.5 m 2dRMS, 95% confidence <sup>1</sup><br>(autonomous, no SA)           |
| Optional Proprietary RTCM:   | < 20 cm 2dRMS, 95% confidence <sup>2</sup>                                  |
| Optional Proprietary L1 RTK: | < 5 cm 2dRMS, 95% confidence <sup>2</sup>                                   |
| Cold Start:                  | 60 sec (no almanac or RTC)  |
| Reacquisition:               | < 1 sec   |
| Maximum Speed:               | 1607 kph (999 mph)  |
| Maximum Altitude:            | 18,288 m (60,000 ft)  |

## Communication

|                                |  |
|--------------------------------|--|
| Ports:                         | Bluetooth, USB 2.0, serial (optional)                  |
| Bluetooth Transmission:        | Class 1, 300 m typical range <sup>3</sup> , up to 1 km |
| Bluetooth Frequency:           | 2.400 – 2.485 GHz                                      |
| Fully Bluetooth Pre-Qualified: | Bluetooth 2.1 + EDR                                    |
| Supported Bluetooth Profiles:  | SPP and iAP  |
| Data I/O Protocol:             | NMEA 0183, Binary                                      |
| Data Output Datum (SBAS):      | ITRF08 (current year epoch)                            |
| Raw Measurement Data:          | Binary and RINEX                                       |
| Correction I/O Protocol:       | RTCM SC-104, Optional Proprietary format               |
| Status LED:                    | Power, GPS, DGPS, DIFF, Bluetooth                      |
| Battery Gas Gauge:             | 5 LED Indicators                                       |

## Power

|                          |  |
|--------------------------|--|
| Battery Type:            | Field replaceable Lithium-Ion pack<br>(Rechargeable in unit or separately) |
| Battery Capacity:        | Battery Operating Time: 15+ hours <sup>4</sup>                             |
| Charging Time:           | 4 hours (vehicle charger available)  |
| Antenna Voltage Output:  | 5 VDC  |
| Antenna Input Impedance: | 50 Ohms  |

## Environmental

|                        |   |
|------------------------|---|
| Operating Temperature: | -40°C to +85°C (-40°F to +185°F) <sup>3</sup> |
| Storage Temperature:   | -40°C to +85°C (-40°F to +185°F)              |
| Humidity:              | 95% non-condensing                            |
| Compliance:            | FCC, CE, RoHS and Lead-free                   |

## Mechanical

|                     |   |
|---------------------|---|
| Enclosure Material: | Xenoy                                       |
| Enclosure Rating:   | Waterproof, IP-67                           |
| Immersion:          | 30 cm, 30 minutes                           |
| Dimensions:         | 12.5 x 8.4 x 4.2 cm (4.92 x 3.3 x 1.65 in.) |
| Weight:             | 372 g (0.82 lbs)                            |
| Data Connectors:    | Mini USB Type B Receptacle                  |
| Antenna Connector:  | SMA Female                                  |

## Antenna

|                         |   |
|-------------------------|---|
| GPS Frequency Range:    | L1 (1575 MHz +/- 10 MHz)                          |
| Gain (without cable):   | 26.5 dB (+/- 2 dB), 35mA                          |
| Voltage:                | +4.5 to + 15 VDC                                  |
| Impedance:              | 50 Ohms   |
| Dimensions:             | 6.6 diam. x 2.7 cm (2.61 x 1.05 in.)              |
| Weight (without cable): | 114 g (0.25 lbs)<br>(with removable magnet mount) |
| Antenna Connector:      | SMA Female  |
| Finish:                 | Fluid Resistant                                   |
| Temperature:            | -55°C to +70°C (-67°F to +158°F)                  |
| Humidity:               | Immersion 30 cm, 30 minutes                       |

## Standard Accessories

|   |
|---|
| Li-Ion Battery Pack (Field replaceable) |
| 12VDC Power Supply                      |
| Belt/Shoulder Carrying Case             |
| Precision Antenna with 1.5 m cable      |
| Soft Hat for antenna                    |
| USB cable                               |


## Field Activated Options

|                            |
|----------------------------|
| 10 Hz or 20 Hz Output rate |
|----------------------------|

### NOTES :

1. Depends on multipath environment, number of satellites in view, satellite geometry, baseline length (for local services) and ionospheric activities
2. Option required on both base and rover. Also requires communication link between base and rover
3. Transmission in free space
4. Lithium-Ion battery performance degrades below -20°C (-4°F)

© Copyright May 2020, Eos Positioning Systems Inc. All rights reserved. Specifications subject to change without notice. Arrow Lite®, Arrow Series® are registered trademarks of Eos Positioning Systems Inc., Canada. The Bluetooth® trademarks are owned by Bluetooth SIG, Inc, U.S.A. All other trademarks are the property of their respective owners.

Made in Canada 

Authorized Distributor



Eos Positioning Systems Inc.  
Terrebonne (Quebec), Canada  
Tel: (450) 824-3325  
[www.eos-gnss.com](http://www.eos-gnss.com) | [info@eos-gnss.com](mailto:info@eos-gnss.com)